

PRODUCT SPECS

GENERATOR MULTIQUIP DA-7000SS

**120/240 V, 1 Ph, 60 Hz
7 kW STANDBY POWER
6 kW PRIME POWER**



SPECIFICATIONS

GENERATOR:

Design Revolving field, self-ventilated, dip-proof single bearing

Number of poles 2 poles

Excitation Statically excited

Standby 7 kW

Prime output 6 kW

Generator 3,600 rpm

Voltage Single phase, 120/240 V

Armature connection .. Series

Voltage regulation 0.05 (no load to full load)

Frequency 60 Hz

Frequency regulation .. 3-5% (no load to full load)

Power factor 1.0

Insulation Class F

Sound level dB(A): 65 (full load at 23 ft)

DIESEL ENGINE:

Make/model Kubota Z482

Emissions Tier 2

Starting system Electric

Design 4 cycle, water-cooled, swirl chamber

Displacement 497 cc

No. of cylinders 2

Bore x stroke (mm) 67 x 68

Gross engine power output 12.5

Hp at rated speed 10.3

Fuel tank capacity 6.6 gal

Fuel consumption:

at full load

• 0.69 gph

at 3/4 load

• 0.55 gph

at 1/2 load

• 0.48 gph

at 1/4 load

• 0.37 gph

Coolant capacity 0.52 gal

Oil capacity 0.54 gal

Battery 12 V 35 A x 1

SIZE AND AMPS:

Dimensions 45" l x 26" w x 32" h

Weight 527 lbs

Electrical Single phase, 120 V, 2-25 A and single phase, 240 V, 25 A



400 Service Road, St. Brieux, SK, S0K 3V0, Canada

1-888-750-1700 | WWW.DRYAIR.CA